



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

1 Identification

- Product identifier

- **Trade name:** Damn Good® Epoxy Putty
- **Synonyms:** All Purpose Aluminum Epoxy Adhesive & Sealant - Part A - Resin
- **Part number:** PS014GA
- **Application of the substance / the mixture** Adhesives

- Details of the supplier of the safety data sheet

- **Manufacturer/Supplier:**
ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com
- **Information department:** Product safety department
- **Emergency telephone number:**
United States: 1-800-424-9300

2 Hazard(s) identification

- Classification of the substance or mixture



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS07

- Signal word

 Warning

- Hazard-determining components of labeling:

Bisphenol-A epoxy resin

- Hazard statements

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash face, hands and any exposed skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
P330 Rinse mouth.
P302+P352 If on skin: Wash with plenty of water.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 1)

P337+P313 If eye irritation persists: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:**- NFPA ratings (scale 0 - 4)****- HMIS-ratings (scale 0 - 4)****- Other hazards****- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

25068-38-6	Bisphenol-A epoxy resin	Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	80 – 89%
14807-96-6	Soapstone		10 – 19%
7429-50-5	Aluminum	Flam. Sol. 2, H228; Water-react. 3, H261	10 – 19%

4 First-aid measures

- Description of first aid measures**- After inhalation:**

Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
 Supply fresh air; consult doctor in case of complaints.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.

- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.

- Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- Extinguishing media**- Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 CO₂, sand, extinguishing powder. Do not use water.
 Use fire fighting measures that suit the environment.

- For safety reasons unsuitable extinguishing agents: Water

- Special hazards arising from the substance or mixture No further relevant information available.

- Advice for firefighters**- Protective equipment:**

Wear self-contained respiratory protective device.
 Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Wear protective clothing.

- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Ensure adequate ventilation.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 2)

Do not flush with water or aqueous cleansing agents
Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities**- Storage:**

- Requirements to be met by storerooms and receptacles:** No special requirements.
- Information about storage in one common storage facility:** Not required.
- Further information about storage conditions:**
Keep receptacle tightly sealed.
Protect from heat and direct sunlight.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

- Control parameters**- Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

14807-96-6 Soapstone

PEL	Long-term value: 20 mppcf ppm (containing <1% Quartz)
REL	Long-term value: 2* mg/m ³ *respirable dust; and <1% Quartz
TLV	Long-term value: 2* mg/m ³ *as respirable fraction; E

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls**- Personal protective equipment:****- General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 3)

- Eye protection:

Tightly sealed goggles

- Body protection: Protective work clothing

* 9 Physical and chemical properties

- Information on basic physical and chemical properties	
- General Information	
- Appearance:	
- Form:	Semi-solid
- Color:	Silver grey
- Odor:	Light
- Odor threshold:	Not determined.
- pH-value:	Not applicable.
- Change in condition	
- Melting point/Melting range:	Undetermined.
- Boiling point/Boiling range:	≥ 260 °C (≥ 500 °F)
- Flash point:	> 260 °C (> 500 °F)
- Flammability (solid, gaseous):	Not determined.
- Decomposition temperature:	Not determined.
- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Product does not present an explosion hazard.
- Explosion limits:	
- Lower:	Not determined.
- Upper:	Not determined.
- Vapor pressure:	Not applicable.
- Density at 20 °C (68 °F):	~ 1.284 g/cm ³ (~ 10.71498 lbs/gal)
- Relative density	Not determined.
- Vapor density	Not applicable.
- Evaporation rate	Not applicable.
- Solubility in / Miscibility with	
- Water:	Insoluble.
- Partition coefficient (n-octanol/water):	Not determined.
- Viscosity:	
- Dynamic:	Not applicable.
- Kinematic:	Not applicable.
- Solvent content:	
- VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
- Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 4)

11 Toxicological information

- Information on toxicological effects

- Acute toxicity:

- Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

14807-96-6	Soapstone	3
------------	-----------	---

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- Behavior in environmental systems:

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- Ecotoxicological effects:

- **Remark:** Toxic for fish

- Additional ecological information:

- General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- Waste treatment methods

- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- UN-Number

- DOT

not regulated

- IMDG, IATA

UN3077

- UN proper shipping name

- DOT

not regulated

- IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (bisphenol-A-(epichlorhydrin); epoxy resin, ALUMINIUM POWDER), MARINE POLLUTANT

- IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (bisphenol-A-(epichlorhydrin); epoxy resin, ALUMINIUM POWDER)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 5)

- Transport hazard class(es)	
- DOT	
- Class	not regulated
- IMDG, IATA	
	
- Class	9 Miscellaneous dangerous substances and articles
- Label	9
- Packing group	
- DOT	not regulated
- IMDG, IATA	III
- Environmental hazards:	
- Marine pollutant:	Product contains environmentally hazardous substances: Aluminum, bisphenol-A-(epichlorhydrin); epoxy resin
- Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
- Special precautions for user	
- Danger code (Kemler):	Warning: Miscellaneous dangerous substances and articles
- EMS Number:	90
- Segregation groups	F-A,S-F
- Stowage Category	Powdered metals
- Stowage Code	A
	SW23 When transported in BK3 bulk container, see 7.6.2.12 and 7.7.3.9.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
	Not applicable.
- Transport/Additional information:	
- IMDG	
- Limited quantities (LQ)	5 kg
- Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g
- UN "Model Regulation":	
	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID, N.O.S. (BISPHENOL-A-(EPICHLORHYDRIN); EPOXY RESIN, ALUMINUM POWDER), 9, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act):

Bisphenol-A epoxy resin

Soapstone

- TSCA new (21st Century Act) (Substances not listed)

7429-50-5 Aluminum

- Proposition 65

- Chemicals known to cause cancer:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 6)

- Chemicals known to cause developmental toxicity:
None of the ingredients is listed.

- Carcinogenic categories
- EPA (Environmental Protection Agency)
None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)
14807-96-6 Soapstone A4

- NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients is listed.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: ND Industries, Inc. - Safety, Health and Environmental Affaires

- Contact: Safety, Health and Environmental Affaires

- Date of preparation / last revision 06/11/2018 / 1

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Sol. 2: Flammable solids – Category 2

Water-react. 3: Substances and mixtures which in contact with water emit flammable gases – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- * Data compared to the previous version altered.

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,

®Vibra-TITE is a registered trademark of ND Industries, Inc.



Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

1 Identification

- Product identifier

- **Trade name:** Damn Good® Epoxy Putty
- **Synonyms:** All Purpose Aluminum Epoxy Adhesive & Sealant - Part B - Hardener
- **Part number:** PS014GB
- **Application of the substance / the mixture** Adhesives

- Details of the supplier of the safety data sheet

- **Manufacturer/Supplier:**
ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com
- **Information department:** Product safety department
- **Emergency telephone number:**
United States: 1-800-424-9300

2 Hazard(s) identification

- Classification of the substance or mixture



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS07

- **Signal word** Warning

- Hazard-determining components of labeling:

Aminophenol

- Hazard statements

H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash face, hands and any exposed skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P301+P312 If swallowed: Call a poison center/doctor if you feel unwell.
P330 Rinse mouth.
P302+P352 If on skin: Wash with plenty of water.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P362+P364 Take off contaminated clothing and wash it before reuse.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P321 Specific treatment (see on this label).

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 1)

P337+P313 If eye irritation persists: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:**- NFPA ratings (scale 0 - 4)****- HMIS-ratings (scale 0 - 4)****- Other hazards****- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

	Mercaptan-terminated polymer	Skin Irrit. 2, H315; Eye Irrit. 2B, H320	80 – 89%
90-72-2	Aminophenol	Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312	1 – 4%

4 First-aid measures

- Description of first aid measures**- General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** Immediately call a doctor.

- Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media**- Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

CO₂, sand, extinguishing powder. Do not use water.

Use fire fighting measures that suit the environment.

- **For safety reasons unsuitable extinguishing agents:** Water

- **Special hazards arising from the substance or mixture** No further relevant information available.

- Advice for firefighters**- Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 2)

Dispose of the collected material according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep receptacle tightly sealed.

- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.

- Control parameters

- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR

- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 3)

* 9 Physical and chemical properties

- Information on basic physical and chemical properties	
- General Information	
- Appearance:	
- Form:	Highly viscous
- Color:	Dark grey
- Odor:	Light
- Odor threshold:	Not determined.
- pH-value:	Not determined.
- Change in condition	
- Melting point/Melting range:	Undetermined.
- Boiling point/Boiling range:	Undetermined.
- Flash point:	> 204.4 °C (> 399.9 °F)
- Flammability (solid, gaseous):	Not applicable.
- Decomposition temperature:	Not determined.
- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Product does not present an explosion hazard.
- Explosion limits:	
- Lower:	Not determined.
- Upper:	Not determined.
- Vapor pressure:	Not determined.
- Density at 20 °C (68 °F):	~ 1.51 g/cm ³ (~ 12.60095 lbs/gal)
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/water):	Not determined.
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
- VOC content:	0.00 % ~ 0.0 g/l / ~ 0.00 lb/gal
- Solids content:	18.0 %
- Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

- LD/LC50 values that are relevant for classification:		
Mercaptan-terminated polymer		
Oral	LD50	2,600 mg/kg (rat)
90-72-2 Aminophenol		
Oral	LD50	500 mg/kg (ATE)

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 4)

Dermal LD50 1,100 mg/kg (ATE)

- Primary irritant effect:

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful
Irritant

- Carcinogenic categories**- IARC (International Agency for Research on Cancer)**

14807-96-6 Soapstone

3

- NTP (National Toxicology Program)

None of the ingredients is listed.

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information**- Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- Behavior in environmental systems:

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- Additional ecological information:

- **General notes:** Generally not hazardous for water

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations**- Waste treatment methods**

- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information**- UN-Number**

- **DOT, ADN, IMDG, IATA** not regulated

- UN proper shipping name

- **DOT, ADN, IMDG, IATA** not regulated

- Transport hazard class(es)

- **DOT, ADN, IMDG, IATA**
- **Class** not regulated

- Packing group

- **DOT, IMDG, IATA** not regulated

- Environmental hazards:

Not applicable.

- Special precautions for user

Not applicable.

- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

- UN "Model Regulation":

not regulated

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 5)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act):

Soda-Lime Glass

Soapstone

Aminophenol

- TSCA new (21st Century Act) (Substances not listed)

Mercaptan-terminated polymer

- Proposition 65

- Chemicals known to cause cancer:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

14807-96-6 Soapstone

A4

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affaires

- **Contact:** Safety, Health and Environmental Affaires

- **Date of preparation / last revision** 06/11/2018 / 4

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Skin Sens. 1: Skin sensitisation – Category 1

- * **Data compared to the previous version altered.**

(Contd. on page 7)

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/11/2018

Reviewed on 06/11/2018

Trade name: Damn Good® Epoxy Putty

(Contd. of page 6)

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,
®Vibra-TITE is a registered trademark of ND Industries, Inc.