



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/02/2016

Reviewed on 10/29/2015

* 1 Identification

- Product identifier

- **Trade name:** Damn Good™ Super Glue Cleaner
- **Synonyms:** 642 Cyanoacrylate Cleaner
- **Part number:** 642DG

- Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

ND Industries, Inc
1000 North Crooks Road
Clawson, MI 48017
USA
Telephone: +1-248-288-0000
Email: info@ndindustries.com
Website: www.ndindustries.com

- Information department:

Product safety department

- Emergency telephone number:

United States: 1-800-424-9300

International: +1-703-527-3887

* 2 Hazard(s) identification

- Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS02 GHS07 GHS08

- **Signal word** Danger

- Hazard-determining components of labeling:

toluene
ethanol
nitromethane

- Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/02/2016

Reviewed on 10/29/2015

Trade name: Vibra-TITE® Cyanoacrylate Cleaner

(Contd. of page 1)

- Precautionary statements

P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P280	Wear protective gloves / eye protection / face protection.
P280	Wear protective gloves.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P271	Use only outdoors or in a well-ventilated area.
P243	Take precautionary measures against static discharge.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:**- NFPA ratings (scale 0 - 4)**

3	Health = 2
3	Fire = 3
2	Reactivity = 3

- HMIS-ratings (scale 0 - 4)

HEALTH 2	Health = *2
FIRE 3	Fire = 3
REACTIVITY 3	Reactivity = 3

- Other hazards**- Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

*** 3 Composition/information on ingredients****- Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

108-88-3	toluene Flam. Liq. 2, H225; Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	30-40%
75-52-5	nitromethane Flam. Liq. 3, H226; Carc. 2, H351; Acute Tox. 4, H302	30-40%
64-17-5	ethanol Flam. Liq. 2, H225; Carc. 1A, H350	20-30%

*** 4 First-aid measures****- Description of first aid measures****- General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** Immediately call a doctor.

- Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

(Contd. on page 3)

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/02/2016

Reviewed on 10/29/2015

Trade name: Damn Good Super Glue Cleaner

(Contd. of page 2)

*** 5 Fire-fighting measures**

- **Extinguishing media**
 - **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
CO2, sand, extinguishing powder. Do not use water.
 - **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
 - **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.
Wear fully protective suit.

*** 6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Wear protective clothing.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

*** 8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- Components with limit values that require monitoring at the workplace:	
108-88-3 toluene	
PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI
75-52-5 nitromethane	
PEL	Long-term value: 250 mg/m ³ , 100 ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/02/2016

Reviewed on 10/29/2015

Trade name: Damn Good Super Glue Cleaner

(Contd. of page 3)

TLV	Long-term value: 50 mg/m ³ , 20 ppm
64-17-5 ethanol	
PEL	Long-term value: 1900 mg/m ³ , 1000 ppm
REL	Long-term value: 1900 mg/m ³ , 1000 ppm
TLV	Short-term value: 1880 mg/m ³ , 1000 ppm
- Ingredients with biological limit values:	
108-88-3 toluene	
BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

- **Additional information:** The lists that were valid during the creation were used as basis.

- Exposure controls**- Personal protective equipment:****- General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.

- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:

Tightly sealed goggles

- Body protection: Protective work clothing

* 9 Physical and chemical properties

- Information on basic physical and chemical properties**- General Information****- Appearance:**

- **Form:** Liquid
- **Color:** Colorless
- **Odor:** Solvent-like
- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/02/2016

Reviewed on 10/29/2015

Trade name: Damn Good Super Glue Cleaner

(Contd. of page 4)

- Change in condition	
- Melting point/Melting range:	Undetermined.
- Boiling point/Boiling range:	101 °C (214 °F)
- Flash point:	4 °C (39 °F)
- Flammability (solid, gaseous):	Not applicable.
- Ignition temperature:	415 °C (779 °F)
- Decomposition temperature:	Not determined.
- Auto igniting:	Product is not selfigniting.
- Danger of explosion:	Heating may cause an explosion.
- Explosion limits:	
- Lower:	1.2 Vol %
- Upper:	63.0 Vol %
- Vapor pressure at 20 °C (68 °F):	59 hPa (44 mm Hg)
- Density at 20 °C (68 °F):	1.11134 g/cm ³ (9.274 lbs/gal)
- Relative density	Not determined.
- Vapor density	Not determined.
- Evaporation rate	Not determined.
- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/water):	Not determined.
- Viscosity:	
- Dynamic:	Not determined.
- Kinematic:	Not determined.
- Solvent content:	
- Organic solvents:	64.0 %
- VOC content:	64.0 %
	711.3 g/l / 5.94 lb/gl
- Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- LD/LC50 values that are relevant for classification:		
108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)
75-52-5 nitromethane		
Oral	LD50	940 mg/kg (rat)
64-17-5 ethanol		
Oral	LD50	7060 mg/kg (rat)
Inhalative	LC50/4 h	20000 mg/l (rat)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** No irritating effect.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/02/2016

Reviewed on 10/29/2015

Trade name: Damn Good Super Glue Cleaner

(Contd. of page 5)

- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

- **Carcinogenic categories**

- IARC (International Agency for Research on Cancer)	
108-88-3 toluene	3
75-52-5 nitromethane	2B
64-17-5 ethanol	1
- NTP (National Toxicology Program)	
75-52-5 nitromethane	R
- OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
 - **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

*14 Transport information

<ul style="list-style-type: none"> - UN-Number - DOT, IMDG, IATA 	UN1993
<ul style="list-style-type: none"> - UN proper shipping name - DOT - IMDG - IATA 	Flammable liquids, n.o.s. (Toluene, Ethanol) FLAMMABLE LIQUID, N.O.S. (TOLUENE, ETHANOL (ETHYL ALCOHOL)) FLAMMABLE LIQUID, N.O.S. (TOLUENE, ETHANOL)
<ul style="list-style-type: none"> - Transport hazard class(es) - DOT 	<div style="text-align: center;">  </div> <ul style="list-style-type: none"> - Class - Label
	3 Flammable liquids 3

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/02/2016

Reviewed on 10/29/2015

Trade name: Damn Good Super Glue Cleaner

(Contd. of page 6)

- IMDG, IATA	
	
- Class	3 Flammable liquids
- Label	3
- Packing group	
- DOT, IMDG, IATA	II
- Environmental hazards:	
- Marine pollutant:	No
- Special precautions for user	
- Danger code (Kemler):	Warning: Flammable liquids 33
- EMS Number:	F-E,S-E
- Stowage Category	B
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
	Not applicable.
- Transport/Additional information:	
- DOT	
- Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
- IMDG	
- Limited quantities (LQ)	1L
- Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	
	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (TOLUENE, ETHANOL), 3, II

*15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

108-88-3 toluene

75-52-5 nitromethane

- TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65

- Chemicals known to cause cancer:

75-52-5 nitromethane

- Chemicals known to cause reproductive toxicity for females:

108-88-3 toluene

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

108-88-3 toluene

64-17-5 ethanol

- Carcinogenic categories

- EPA (Environmental Protection Agency)

108-88-3 toluene

II

- TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene

A4

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/02/2016

Reviewed on 10/29/2015

Trade name: Damn Good Super Glue Cleaner

(Contd. of page 7)

75-52-5	nitromethane	A3
64-17-5	ethanol	A3

- NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affairs

- **Contact:** Safety, Health and Environmental Affairs

- **Date of preparation / last revision** 05/02/2016 / 3

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Carc. 1A: Carcinogenicity – Category 1A

Carc. 2: Carcinogenicity – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

- *** Data compared to the previous version altered.**

- **Disclaimer**

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,

®Damn Good is a registered trademark of ND Industries, Inc.